

Declaration of Performance

Construction Products (Amendment etc.) (EU Exit) Regulations 2020 No. 1359

UKCA DoP 111									
1	Hamberger multi layer parquet, 2-layer-parquet							EN 13489:2017	
2	Floor covering for internal use under dry conditions								
3	Hamberger Floo	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim NDS 08-821							
4	System of assessm	nent and verification of constancy of performance						3 *)	
5	Thickness	9 mm	9 mm (HDF)	10 mm	10,5 mm (HDF)	11 mm	12 mm		
	Mass density	> 500 kg/m³							
	Key properties								
	Reaction to fire *)	D _{fl} - s1						BS EN 14342:2013	
	Emission of formaldehyde *)	E1							
	Content of PCP	≤ 5 x 10 ⁻⁶ⁿ							
	Emission of other dangerous substances	NPD							
	Breaking strength	NPD							
	Slip resistance	NPD							
	Thermal conductivity [W/(m·K)]	0,120	0,186	0,123	0,183	0,121	0,133		
	Natural durability	Class 5 (EN 350-1)							
6	The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).								
	Signed for and on behalf of the manufacturer								
	Peter Huber, head of production production								
	Stephanskirchen, 20.06.2022								

In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0321 SATRA, United Kingdom) has/have performed type testing according to the system specified in (4).