



Declaration of Performance
Construction Products (Amendment etc.)
(EU Exit) Regulations 2020 No. 1359

UKCA DoP 114

1	Hamberger multi layer parquet, 3-layer-parquet	EN 13489:2017
---	--	------------------

2	Floor covering for internal use under dry conditions
---	--


3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim NDS 08-821
---	---

4	System of assessment and verification of constancy of performance	3 ^{*)}
---	---	-----------------

5	Thickness	11 mm (HDF)	12 mm	12 mm (HDF)	13,5 mm	Silent CT +2 mm	BS EN 14342:2013	
	Mass density	> 500 kg/m ³						
	Key properties							
	Reaction to fire ^{*)}	D _{fl} - s1						
	Emission of formaldehyde ^{*)}	E1						
	Content of PCP	≤ 5 x 10 ⁻⁶ⁿ						
	Emission of other dangerous substances	NPD						
	Breaking strength	NPD						
	Slip resistance	NPD						
	Thermal conductivity [W/(m·K)]	0,174	0,117	0,172	0,119	+0,050		
	Natural durability	Class 5 (EN 350-1)						

6 The performance of the product identified in (1) is in conformity with the declared performance in (5).
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,
head of production 

Stephanskirchen, 20.06.2022

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0321 SATRA, United Kingdom) has/have performed type testing according to the system specified in (4).