



Declaration of Performance
Construction Products (Amendment etc.)
(EU Exit) Regulations 2020 No. 1359


UKCA DoP 118

1	Manufaktur multi layer parquet	EN 13489:2017
2	Floor covering for internal use under dry conditions	
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim NDS 08-821	
4	System of assessment and verification of constancy of performance	3 ^{*)}

5	Thickness	Carré 16 mm	XL 18 mm	Tile 18 mm	BS EN 14342:2013	
	Mass density	> 500 kg/m ³				
	Key properties					
	Reaction to fire ^{*)}	D _{fl} - s1				
	Emission of formaldehyde ^{*)}	E1				
	Content of PCP	≤ 5 x 10 ⁻⁶ⁿ				
	Emission of other dangerous substances	NPD				
	Breaking strength	NPD				
	Slip resistance	NPD				
	Thermal conductivity [W/(m·K)]	0,133	0,118	0,15		
	Natural durability	Class 5 (EN 350-1)				

6 The performance of the product identified in (1) is in conformity with the declared performance in (5).
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,
head of production 

Stephanskirchen, 20.06.2022

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0321 SATRA, United Kingdom) has/have performed type testing according to the system specified in (4).