




**Declaration of Performance**  
Construction Products (Amendment etc.)  
(EU Exit) Regulations 2020 No. 1359

UKCA DoP 139

1	Hamberger multi layer parquet, 3-layer-parquet	EN 13489:2017	
2	Floor covering for internal use under dry conditions		
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim NDS 08-821		
4	System of assessment and verification of constancy of performance	3 <sup>*)</sup>	
5	Thickness	13,5 mm	BS EN 14342:2013
	Mass density	> 500 kg/m <sup>3</sup>	
	Key properties		
	Reaction to fire <sup>*)</sup>	C <sub>fl</sub> - s1	
	Emission of formaldehyde <sup>*)</sup>	E1	
	Content of PCP	≤ 5 x 10 <sup>-6n</sup>	
	Emission of other dangerous substances	NPD	
	Breaking strength	NPD	
	Slip resistance	NPD	
	Thermal conductivity [W/(m·K)]	0,123	
Natural durability	Class 5 (EN 350-1)		
6	The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).  Signed for and on behalf of the manufacturer  <i>Peter Huber,</i> <i>head of production</i>   <i>Stephanskirchen, 05.12.2022</i>		
*) In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0765 WKI Braunschweig, NB 0766 eph) has/have performed type testing according to the system specified in (4).			