


UKCA DoP 150

1	Design floor covering	EN 16511: 2019
2	Floor covering for internal use under dry conditions	
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim 4018427 03 08	
4	System of assessment and verification of constancy of performance	3 <sup>*)</sup>

5	Thickness	8 mm with cork insulation	9,8 mm	8 mm	BS EN 14041:2004/AC:2006	
	Key properties					
	Reaction to fire <sup>*)</sup>	C <sub>fl</sub> - s1	D <sub>fl</sub> - s1	C <sub>fl</sub> - s1		
	Emission of formaldehyde <sup>*)</sup>	E1				
	Emission of VOC	≤ 0,025 mg/m <sup>3</sup>				
	Content of dangerous substances	Compliant, not actively added				
	Water resistance	NPD				
	Slip resistance	μ ≥ 0,30				
	Electrical behaviour	NPD		Antistatic		
	Thermal conductivity	0,143 W/(m·K)	0,147 W/(m·K)	0,125 W/(m·K)		
Durability as regards reaction to fire	NPD					

6 The performance of the product identified in (1) is in conformity with the declared performance in (5).  
This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

*Peter Huber,*  
head of production 

Stephanskirchen, 20.06.2022

<sup>\*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 0321 SATRA, United Kingdom) has/have performed type testing according to the system specified in (4).