

19

Declaration of Performance (Regulation (EU) No 305/2011)

DoP 159

1	Manufaktur multi-layer parquet Chevron EN 1348 2017		EN 13489: 2017
2	Floor covering for internal use under dry conditions		
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim		
4	System of assessment and verification of constancy of performance		3 ^{*)}
	Thickness	9,8 mm	
5	Mass density	>500 kg/m³	
	Key properties		
	Reaction to fire *)	C _{fl} - s1	EN 14342: 2013
	Emission of formaldehyde *)	E1	
	Content of PCP	≤ 5x10 ⁻⁶ⁿ	
	Emission of other dangerous substances	NPD	
	Breaking strength	NPD	
	Slip resistance	NPD	
	Thermal conductivity	0,17 W/mK	
	Natural durability	5 (DIN EN 350:2016)	

The performance of this product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber, head of production

6

Stephanskirchen, 29.06.2022

ppalul

^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 1322 IBS Linz) has/have performed type testing according to the system specified in (4).