




**Declaration of Performance**

Construction Products (Amendment etc.)  
(EU Exit) Regulations 2020 No 1359

UKCA DoP 162

1	Wall Design Wood				EN 14915:2013 +A2:2020
2	Siding for internal use under dry conditions				
3	Hamberger Flooring GmbH & Co.KG, Postfach 100353, D-83003 Rosenheim NDS 08-821				
4	System of assessment and verification of constancy of performance				3 <sup>*)</sup>
5	Thickness	3,7 mm	4,7 mm	7,3 mm	11,2 mm
	Key properties				
	Reaction to fire	E			
	Emission of formaldehyde <sup>*)</sup>	E1			
	Content of PCP	$\leq 5 \times 10^{-6}n$			
	Emission of other dangerous substances <sup>*)</sup>	NPD			
	Fixing resistance	NPD			
	Acoustic absorption	NPD			
	Durability class (EN 350)	Class 5			
	Thermal conductivity design wood	0,155 W/(m·K)		0,123 W/(m·K)	
Thermal conductivity ComforTec	+ 0,050 W/(m·K)				
<p>The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).</p>					
6	<p>Signed for and on behalf of the manufacturer</p> <p><i>Peter Huber,</i> head of production </p> <p>Stephanskirchen, 20.06.2022</p>				
<p><sup>*)</sup> In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut) has/have performed type testing according to the system specified in (4).</p>					

BS EN 14915:2013