



17

Declaration of performance
(Regulation (EU) Nr. 305/2011)

DoP 162

1

Siding for internal use under dry conditions

EN 14915:
2013+A1:2020

2

Wall Design Wood

3

Hamberger Flooring GmbH & Co.KG, Postfach 100353, 83003 Rosenheim
NDS 08-821

4

System of assessment and verification of constancy of performance

3^{*)}

Thickness

3,7 mm

4,7 mm

7,3 mm

11,2 mm

Key properties

Reaction to fire

E

Emission of formaldehyde ^{*)}

E1

PCP concentration

 $\leq 5 \times 10^{-6n}$ Emission of other dangerous substances ^{*)}

NPD

Acoustic absorption

NPD

Thermal conductivity Design wood

3,7 / 4,7 / 7,3 mm: 0,155 W/mK
11,2 mm: 0,123 W/mK
ComforTec: + 0,050 W/mK

Fixing resistance

NPD

Natural durability

5
(DIN EN 350)

EN 14915:2013

6

The performance of the product identified in (1) is in conformity with the declared performance in (5). This declaration of performance is issued under the sole responsibility of the manufacturer (3).

Signed for and on behalf of the manufacturer

Peter Huber,
*Head of production**Stephanskirchen, 29.06.2022*^{*)} In accordance with the harmonised standard specified in (5), the inspection body/bodies (NB 2097 eco-Institut) has/have performed type testing according to the system specified in (4).