


## Parquet Data Sheet

### HARO PARQUET 3500, Plank 1-Strip 180 and Longstrip

#### Construction

HARO PARQUET 3500, Plank 1-Strip 180 and Longstrip is a high-quality multilayer parquet product by Hamberger Flooring GmbH & Co. KG with the following construction:

1. Surface finish: *permaDur* natural matt finish or *naturalLin* natural oil surface
2. Top layer:  $\geq 2.5$  mm ( $3/32''$ ) thick precious wood layer
3. Middle layer: HDF E1 coreboard
4. Backing board: Softwood veneer
5. Back of the board: Optional Silent Pro® insulation layer or ComforTec



#### Dimensions and moisture behavior

All data refer to the delivery humidity of 5 - 9% according to EN 13183-1.

Length	Width	Total thickness	Top layer thickness	equilibrium humidity at 23 ° C and 50% RH
EN 13647	EN 13647	EN 13647	EN 13647	EN 13183-1
2200mm ( $86^{39}/64''$ )	180 mm ( $7^{3}/32''$ ) (SB, LHD)	approx. 12 mm ( $15/32''$ )	$\geq 2,5$ mm ( $3/32''$ )	6,0%
maximum deviation: $\pm 1$ mm (DIN EN 13489: $\pm 0,1$ %)	maximum deviation: $\pm 0.1$ mm (DIN EN 13489: $\pm 0.2$ mm)	(DIN EN 13489: no information)	maximum deviation: $\pm 0.2$ mm (DIN EN 13489: $> 2.5$ mm)	maximum deviation: $\pm 0.5$ % (DIN EN 13489: no information)

#### Installation system

The patented glueless installation system provides an easy, perfect-fit and permanent installation of the parquet floor.



On the long sides: Angle-in to lock it  
On the short sides: Top Connect 5G

#### Surface finish

HARO PARQUET 3500, Plank 1-Strip 180 and Longstrip can optionally be provided with one of the following surface refinements:

	<b>permaDur</b> VERSIEGELUNG	<b>naturalLin plus</b> NATURÖL-OBERFLÄCHE	
Character	Hard-wearing finish	Natural oil surface that allows the wood to breathe	
Ingredients	Performance-optimised acrylic resin	Ingredients based on renewable raw materials	
How it works	High-grade, UV-cured acrylic resins coat the wood with a 40-50 $\mu$ m thick protective varnish, making the parquet surface resistant to abrasion, scratches and stains.	The floor care oil is based on natural ingredients. It penetrates deep into the pores of the wood and protects the parquet floor from dirt and from drying out. The wood can breathe and retains its natural look and feel.	

## Performance specifications



Reaction to fire [DIN EN 13501-1]	Slip resistance [EN 13893]	Formaldehyde emissions [DIN EN 717-1]	VOC emissions [AgBB-Scheme/Blue Angel]
C <sub>fi</sub> -s1	R9 / R10	≤ 0.05 ppm	≤ 300 ppm
C <sub>fi</sub> = flame-resistant	fulfils the requirements of occupational safety in accordance with BGR 181; please follow the installation instructions	Evidence of emissions for: - Blue Angel (RAL UZ 176) - DGNB ENV 1.2, quality level 4, criteria matrix 47a <a href="http://www.dgnb-navigator.de">www.dgnb-navigator.de</a> - LEED v.1 Option 2 & Leed v4 for projects outside U.S; EQ credit low-emitting materials - BREEAM Hea02 Indoor air Quality, exemplary level emission criteria for wood flooring (table 18)	

Bond strength [DIN EN 204]	Thermal resistance	Weight per unit area	Castor chair resistance [EN ISO 4918]
≥ D3	0.070 m <sup>2</sup> k/W	9,87 kg/m <sup>2</sup>	> 25000 cycles
D3 = Stress group for indoor areas of high quality	Thermal conductivity value; limit value max. for underfloor heating is 0.15 m <sup>2</sup> k/W	Wood is a natural material and affected by growth-related density variations. Therefore the data may slightly differ.	no changes in bond strength or impairment of the connection system.

\*) See separate information about the fire prevention class and slip resistance

## Insulation layer


The parquet can optionally be provided with a Silent Pro® insulation layer or with ComforTec. Please pay attention to the data sheets of the insulation layer.

	Thickness	Thermal resistance	Indoor sound improvement	Footfall improvement
	approx. 2 mm / 3/32"	0.01 m <sup>2</sup> K/W	approx. 30%	approx. 18 dB
	approx. 2 mm / 3/32"	0.04 m <sup>2</sup> K/W	approx. 60%	approx. 14 dB

## Quality label



[www.blauer-engel.de/uz176](http://www.blauer-engel.de/uz176)



[www.ibu-epd.com](http://www.ibu-epd.com)