

Technical Information EPS Easy Aqua Stop

ID no. 407 719

HARO
Quality Flooring

Product Polystyrene foam folding plate with integrated moisture protection and AluTape

Product composition Expanded polystyrene foam + AluTape moisture protection

Advantages

- Ingeniously easy to install
- Suitable for use with underfloor heating

Installation

- Easy and dust-free to cut to size with a general-purpose cutter (carpet knife)
- Fit the ends together tightly; do not overlap or leave gaps
- Ends fitted with aluminium adhesive tape

Environment

- Can be disposed with domestic waste
- Free from plasticisers

Technical data



CEN/TS 16354	Thickness	1.6 mm (+/- 15 %)
	Punctual conformability (PC)	≥ 1 mm
	Compressive strength (CS)	~ 60 kPa
	Compressive creep (CC)	≥ 5 kPa
	Dynamic load (DL)	≥ 100,000 cycles
	Resistance to large ball (RLB)	≥ 900 mm
	Water vapour diffusion resistance (SD)	≥ 100 m
	Thermal resistance (R)	~ 0.040 m ² K/W
	Impact sound reduction (IS)	≤ 20 dB
	Reaction to fire (RTF)	E _{fl}
	Suitable for underfloor heating	Yes
Weight per unit area	0.046 kg/m ²	
Weight	approx. 30 kg/m ³	
Dimensions	1.20 x 15 m	
Content/pack	18 m ²	
Content/pallet	378 m ² (21 packs)	
Packaging	Individual packs wrapped in foil with guide lines 21 packs on a Euro pallet	
Fulfils <u>all</u> minimum technical requirements in accordance with EPLF		
in accordance with MMFA (Group 1)		
	Yes	
	Yes	

This technical information is for your guidance and support and is based on our most up-to-date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG
P.O. Box 10 03 53
D-83003 Rosenheim, Germany
www.haro.com

Phone +49 8031 700-0
Fax +49 8031 700-299
E-mail: mail@hamberger.de