

Technical Information

C22 Paint Pen

Art. No. 405 554

405 555

405 556

405 557

HARO®

Quality Flooring

Application area	C22 Paint Pen with lightfast and weatherproof paint for indoor and outdoor use on wood, plastic and metal surfaces. The quick and easy way to touch up edges, corners, bevelled edges and minor scratches.	
Product properties	<ul style="list-style-type: none">- Paint quality meets the requirements of the German VOB standard (2 years) - when applied according to manufacturer's instructions.- Strongly pigmented, acrylic resin based topcoat.- Lightfast and weatherproof.- Covers well even when applied thinly.- Fast drying.- Not resistant to soft-PVC degradation.	
Test Standards	Dust dry:	After 1-2 min. Tack-free after approx. 5 min., depending on room temperature.
	Lightfastness and weather resistance:	good
	Adhesion:	Good/very good (exception: conditionally good on UV-cured paint systems).
	Suitability:	for almost all paint and powder coatings.
	Recoatibility:	Excellently recoatable with all paints.
Safety Advice	<ul style="list-style-type: none">- Keep out of the reach of children.- Highly flammable.- Harmful by inhalation and in contact with skin.- Irritating to eyes, respiratory system and skin.- Keep away from sources of ignition – No smoking.- In case of contact with eyes, rinse with plenty of water and seek medical advice.- Use only in well-ventilated areas.- Do not breathe vapour.	
Information on Occupational Health and	<ul style="list-style-type: none">- The C22 Paint Pen is listed in the Hazardous Substances Directive and subject to the Dangerous Goods Regulations.- Please request the Material Safety Data Sheet, if required.	
Disposal Considerations	<ul style="list-style-type: none">- Do not allow the C22 Paint Pen to enter drainage/sewage system.- Do not dispose of in domestic waste.- Product residues can be disposed of in accordance with waste code 080102.- For detailed information, please refer to the Material Safety Data Sheet or ask your local waste management authorities.	

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG

Postfach 10 03 53

D-83003 Rosenheim

www.haro.com

Phone +49 8031 700-0

Fax +49 8031 700-299

E-mail: mail@hamberger.de