

Technical information

Hard wax-kit

Art. No. 405 865
405 866
405 867

Uses

- For the repair of minor and medium-severe damage on a flat surface or on an edge.
- To be used on surfaces that are subject to medium-severe use.
- For solid wood, veneer, foil, thermosetting, thermoplastic and plastic surfaces for interior use.
- Recommended for indoor use.

Characteristics

- Mixture of mineral waxes, coloured with earth and oxide dyes.
- Good adhesion properties.
- Colour shades to be intermixed during melting.
- Can be stripped off easily by means of the Specia Fillers Applicator, a chisel or the Metal Planer.

Specifications

Softening point:	76°C (ISO 2207)
Dropping point:	81°C (DIN 51 801)
Mechanical stability:	good
Adhesion:	good adhesion to all plastics, soft and hard woods.
Shelf life:	unlimited

Safety precautions

- The product is not subject labelling in terms of the Council Directive Regulation 67/548/EEC article 23.
- Keep out of reach of children.

This technical information is for your guidance and is based on our most up to date knowledge. This is not an assurance of the properties of the described product with regard to the legal provisions of the Guarantee.

Hamberger Flooring GmbH & Co. KG

Postfach 10 03 53
D-83003 Rosenheim
www.haro.com

Phone +49 8031 700-0
Fax +49 8031 700-299
E-mail: mail@hamberger.de