

Technical information

HARO premium PE foam DS

ID No. 411 492

HARO
Quality Flooring

Product	First-class premium PD foam with integrated vapour barrier, which withstands significant traffic and load.
Product composition	Permanently flexible underlay material with integrated vapour barrier
Advantages	<ul style="list-style-type: none">- Permanently flexible- Footfall sound absorbing- Compression resistant- Waterproof
Installation	<ul style="list-style-type: none">- The surfaces onto which the PE foam is applied must meet the static, thermal, moisture and acoustic requirements- Easy and dust-free to cut to size with a general-purpose cutter (carpet knife)- Fit the ends together tightly; do not overlap or leave gaps- Ends fitted with aluminium adhesive tape
Environment	<ul style="list-style-type: none">- The product is ecological and contains no toxic substances.- 100% recyclable

Weight per unit area	0.14 kg/m ²
Weight	100 kg/m ³ (+/- 10 %)
Dimensions	30.0 x 1.0 m
Roll coverage	30 m ²
Content/pallet	360 m ² (12 rolls)
Packaging	Individual rolls wrapped in foil with guide lines 12 rolls on a Euro pallet

Technical data



CEN/TS 16354	Thickness	approx. 2 mm (+/- 10%)
	Punctual conformability (PC)	2.0 mm
	Compressive strength (CS)	> 65 kPa
	Compressive creep (CC)	> 25 kPa
	Dynamic load (DL)	100,000 cycles
	Resistance to large ball (RLB)	-
	Water vapour diffusion resistance (SD)	-
	Thermal resistance (R)	> 0.05 m ² K/W
	Impact sound reduction (IS)	19 dB
	Reaction to fire (RTF)	E _{fl}
	Suitable for underfloor heating	Yes
	Fulfils <u>all</u> minimum technical requirements in accordance with EPLF in accordance with MMFA (Group 1)	Yes Yes

This technical data is provided for your information and guidance and is based on the current state of the described product within the

Hamberger Flooring GmbH & Co. KG

Postfach 10 03 53
83003 Rosenheim
www.haro.de

Phone +49 8031 700-0
Fax +49 8031 700-299
E-mail: mail@hamberger.de