

Technical information

Roll-out cork DS

ID No. 411 475

HARO
Quality Flooring

Product Universal natural product with an integrated moisture barrier for sound and heat insulation

Product composition Insulation underlay made from natural cork

Advantages

- 100% natural, reusable and recyclable
- Exceptional acoustic characteristics
- Excellent thermal resistance ability
- Flexible and adaptable
- Outstanding durability

Installation

- Install with the vapour barrier foil side up
- Easy to cut and dust-free
- Fit the ends together tightly; do not overlap or leave gaps
- Ends fitted with aluminium adhesive tape

Environment

- The product is made from pure natural cork

Technical data



CEN/TS 16354	Punctual conformability (PC)	> 1.3 mm
	Compressive strength (CS)	470 kPa
	Compressive creep (CC)	50 kPa
	Dynamic load (DL)	> 100,000 cycles
	Resistance to large ball (RLB)	-
	Thermal resistance (R)	0.039 m ² K/W
	Impact sound reduction (IS)	19 dB
	Reaction to fire (RTF)	E _{fl}
	SD value	≥ 90 m
	Suitable for underfloor heating	Yes
Gross weight	0.32 kg	
Dimensions	1.0 x 30.0 m ²	
Roll coverage	30 m ²	
Content/pallet	360 m ² = 12 rolls	
Packaging	Individual rolls wrapped in foil with guide lines 12 rolls on a Euro pallet	
Fulfils <i>all</i> minimum technical requirements in accordance with EPLF		Yes
in accordance with MMFA (Group 1+2)		Yes

This technical data is provided for your information and guidance and is based on the current state of our knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG
Postfach 10 03 53
83003 Rosenheim
www.haro.com

Phone +49 8031 700-0
Fax +49 8031 700-299
E-mail: mail@hamberger.de