

Technical Information Roll-out Cork Underlay

ID no. 403 640/402 847

HARO
Quality Flooring

Product	Natural product with excellent price/performance ratio
Product composition	2 mm insulation underlay made from natural cork
Advantages	<ul style="list-style-type: none">- General purpose application- Also suitable for use in rooms with computer systems- Excellent price/performance ratio
Installation	<ul style="list-style-type: none">- Use PE film as an underlay on all mineral subfloors- Easy and dust-free to cut to size with a general-purpose cutter (carpet knife)
Environment	<ul style="list-style-type: none">- The product is made from pure natural cork- Free from flame retardants, fungicides, heavy metals and formaldehyde

Technical data	Thickness	approx. 2 mm
	Punctual conformability (PC)	-
	Compressive strength (CS)	-
	Compressive creep (CC)	-
	Dynamic load (DL)	-
	Resistance to large ball (RLB)	-
	Water vapour diffusion resistance (SD)	-
	Thermal resistance (R)	0.041 m ² K/W
	Impact sound reduction (IS)	17 dB
	Reaction to fire (RTF)	E _{fl}
	Suitable for underfloor heating	Yes
	Weight per unit area	0.40 kg/m ²
	Weight	180 kg/m ³
ID no. 403 640	Dimensions	10 x 1 m
	Roll coverage	10 m ²
	Content/pallet	350 m ² (35 rolls)
	Packaging	Individual rolls wrapped in foil with guide lines 35 rolls on a Euro pallet
ID no. 402 847	Dimensions	30 x 1 m
	Roll coverage	30 m ²
	Content/pallet	360 m ² (12 rolls)
	Packaging	Individual rolls wrapped in foil with guide lines 12 rolls on a Euro pallet
	Fulfils <i>all</i> minimum technical requirements in accordance with EPLF in accordance with MMFA (Group 1)	Yes Yes

This technical information is for your guidance and support and is based on our most up-to-date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.