

Technical information
Skirtings PS foam waterproof

ID no. 409780, 410641

Product:	Skirtings with foamed PS as substrate, film coated	
Product composition:	foamed PS as substrate with a printed film	
Installation/assembly:	Fastening with Haro wall clip 407198 -> for skirtings with clip bevel Fastening with Haro assembly adhesive 409847 or Haro nail clip 410634 -> for skirtings without clip bevel Fastening with screws and nails -> an option for all skirtings	
Specifications:	Substrate	Foamed PS
	Surface	Gravure-printed film or digitally printed film
	Length tolerance	+/- 15mm
	Dimension tolerance T/W < +/-	-0.8mm
	Dimension tolerance T/W ≥ +/-	5.4% of the relevant profile cross-section
	Bowing	Height: max. 10 mm/running meter; professional further processing must be possible
	Twisting	Height ≤ 10 mm /running meter; professional further processing must be possible
	Material thickness	400 - 600 kg / m ³ , depending on filling degree
	Paper film	Melamin-urea resin impregnated style paper made of high-quality cellulose with a surface coating Light fastness: 7 on the Blue Wool Scale Gloss level: 8 – 20 units at a 60° measuring angle Abrasion resistance: ≥ 250 U as per
	Applying masking tape to sk	Only commercially available masking tape may be used on the skirting board for paintwork. This must be removed after 16 hours at the latest.
	Storage	Vertical or horizontal, protect from direct sunlight, Ideal climate: 18°C/55-70% rel. humidity
	Skirting-board labelling	Board label with article number, bar code,

This technical data is provided for your information and guidance and is based on the current state of our knowledge. It does not represent any assurance of the described product's properties in terms of statutory warranty regulations.