

Technical information

HARO Repair putty set - Reparation Lacquer

Art. No. 405 840	405 845
405 841	405 846
405 842	405 847
405 844	405 848

Product description Reparation Laquer is a 1-component water based laquer for surface treatment of wood- and parquet flooring as well as other wooden interiors. Excellent sealer to reparations filled with "Putty" (also in the HARO Repair putty set).

Characteristics

- It's easy to use
- High resistance to scratches and heels
- High resistance to chemicals

Technical data

Type of lacquer: 1-component water based PU / acrylate copolymer

Dry substance: Ca 30%

Volatile Organs
Compound: max 60 g / l VOC

Viscosity: Ca 20 sec (25°C, FC4)

Wearing qualities: Ca 8 mg/100 spins (SIS 923509)

Gloss: Glossy ca 85, semi matte ca 45, matte 25 (approx. values)

Drying time: 1-2 hours at 20°C / 60% R.H.

Coverage: 8 - 10 m²/l (100-120 g/m²) per application

Harmful: Not a classified product

Flammability: Not a classified product

Storage time: 1 year in not opened original packaging

Frost resistant: To be kept away from frost. Once frozen, the lacquer can not be used.

Packaging: 12 x 30 ml

Preparations

The surface to be treated with reparations lacquer should be clean, well grinded, dry and free from waxes and other impurities. Use lacquer which has adapted room temperature. The temperature must not fall below 13°C, neither on the surface nor the lacquer. Before lacquering a damage/repared damage the surface must be grinded. Do not cover the damage with rugs or cloths until a week after application.

This technical information is for your guidance and is based on our most up to date knowledge. This is not an assurance of the properties of the described product with regard to the legal provisions of the Guarantee.