

Technical Information

HARO Caulking Cork - solvent free

Art. No. 406 088

Product	<p>HARO Caulking Cork - solvent-free is a universal, high-grade sealant for sound and heat insulation. The material consists of granulated cork and a solvent-free elastic binder.</p> <p>HARO Caulking Cork - solvent-free is a one-component product, viscoplastic and stable. The many air-filled cells in the granulated cork make HARO Caulking Cork - solvent-free an insulating material that not only effectively reduces the transfer of heat and cold, but also provides excellent sound insulation.</p>
Application area	<p>HARO Caulking Cork - solvent-free is suitable for the sound and heat insulation of joints between window frame and wall, at doors and partition walls as well as for other possible sound and heat insulation applications.</p>
Advantages	<ul style="list-style-type: none">- Solvent-free- Odourless
Technical data	<p>Base: Cork granulate, bound together with solvent-free adhesive</p> <p>Colour: cork colour (when dry)</p> <p>Non-sag properties: non-sagging</p> <p>Specific weight: Approx. 0.6 g/cm³ (wet, DIN 52451-PY)</p> <p>Curing system: by drying</p> <p>Fully cured after: Approx. 24-48 hours, depending on joint geometry and air humidity.</p> <p>Temperature stability: Approx. - 40 °C to + 90 °C</p> <p>Working temperature: + 5 °C to + 35 °C (component temperature)</p> <p>Shelf life: 12 months when stored in unopened original container. Store in a cool, dry place between + 5 °C and 35 °C.</p>
Coverage	<p>One 500 ml sausage pack seals approx. 5 metres of joints with a cross section of 10 x 10 mm². The coverage is calculated approx. as follows: joint width (mm) x joint depth (mm) = ml per metre of joint.</p>
Instructions	<p>Apply evenly while pressing against the joint sides. The joints must be filled evenly. Once opened, the product should be used up as soon as possible.</p>

This technical information is for your guidance and is based on our most up to date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG

Postfach 10 03 53

D-83003 Rosenheim

www.haro.com

Phone +49 8031 700-0

Fax +49 8031 700-299

E-mail: mail@hamberger.de