

## **Technical information**

### **Soft wax C12**

Art. No. 405 576	405 580
405 577	405 581
405 578	405 582
405 579	

---

- Uses**
- For the repair of scratches, cracks, holes and pressure marks on a flat surface
  - For solid woods, veneers, foils, plastic surfaces for interior use
  - For surfaces that are not subject to severe use
  - Recommended for indoor use

- Characteristics**
- Mixture of mineral waxes, coloured with earth and oxide dyes.
  - Easy to apply.
  - Colours can be intermixed.
  - Limited mechanical resistance.
  - Limited heat resistance.

**Specifications**

<b>Softening point:</b>	76°C (ISO 2207)
<b>Dropping point:</b>	81°C (DIN 51 801)
<b>Mechanical stability:</b>	limited, wax warps under high mechanical stress.
<b>Adhesion:</b>	good adhesion to all above substrates.
<b>Shelf life:</b>	unlimited (stored at room temperature, in original unopened container).

- Safety precautions**
- The product is not subject to specific labelling in terms of the Council Directive Regulation 67/548/EEC article 23.
  - Keep out of reach of children.

This technical information is for your guidance and is based on our most up to date knowledge. This is not an assurance of the properties of the described product with regard to the legal provisions of the Guarantee.

---

**Hamberger Flooring GmbH & Co. KG**

Postfach 10 03 53

83003 Rosenheim

[www.haro.de](http://www.haro.de)

Tel. +49 8031 700-0

Fax +49 8031 700-299

E-Mail: [mail@hamberger.de](mailto:mail@hamberger.de)