

Technical Information

aqua shield

Art. no. 409 774

Product	Floor care for sealed parquet floors and coated surfaces. - Refreshes floor surfaces on a permanent basis - Increases durability - Protects against penetrating moisture from above	
Application	The floor must be cleaned thoroughly (dust-free) before applying clean & green aqua shield. We recommend clean & green active for this job. Thoroughly shake the clean & green aqua shield floor-care product before use. Then pour it, undiluted, into a bucket. Then apply clean & green aqua shield with the "Wischwiesel" flat wet-mop, spreading the cleaner in uniformly deep and overlapping lines over the floor. Always apply lengthways, in the board direction. Wait about 2 hours before subjecting the floor to traffic and load.	
Contents	Synthetic dispersions that contain no metallic salts (TBEP-free), polyethylene waxes, water-soluble solvents. Contains: 2-Methyl-2H-isothiazol-3-On 1,2-Benzisothiazol-3(2H)-on	
Technical data	pH value:	Approx. 8.0
	Giscode:	GH10
	Coverage:	1,000 ml cover approx. 35 m ²
	Shelf life:	3 years
	Colour:	Milky, beige
	State:	Liquid
Note:	<ul style="list-style-type: none"> - Keep out of reach of children. - Do not eat, drink or smoke when using. - Protect from draughts during application. - Afterwards ensure there is thorough ventilation for drying. - In case of contact with the eyes or skin, rinse immediately with plenty of water. - Do not allow to enter waterway systems, drainage/sewage or soil. - Only completely empty packaging can be recycled. - Dispose of liquid product residues at local collection point. - Not suitable for spraying. - Use a P2 dust filter when grinding. - To reduce floor slipperiness, we recommend that you regularly clean the area with clean & green natural. - Use opened containers quickly. - Close containers immediately after use. - Protect from frost. - The application of aqua shield creates a new layer of protection, one that revitalises the appearance of the surface and adds new gloss - Clean work materials with water and soap immediately after use. 	



www.blauer-engel.de/uz12a

This technical information is for your guidance and support and is based on our most up-to-date knowledge. It makes no representation or warranty, express or implied, as to any specific properties of the described product within the meaning of the statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG

P.O. Box 10 03 53

83003 Rosenheim

www.haro.de

Phone +49 8031 700-0

Fax +49 8031 700-299

E-mail: mail@hamberger.de