

Technical information

HARO naturaLin Oil

Item no. 412 577

Product	naturaLin Oil is a care finish and provides added protection and hence the basis for regular cleaning and care. NaturaLin Oil increases scratch resistance and is water-repellent. The surface remains vapour-permeable and open-pored. If the floor shows traces of use over time, you can carry out intensive care once again with naturaLin Oil.
Ingredients	Oil derived from linseed oil as well as alkyd resin modified with natural oil along with lead- and cobalt-free desiccants, tough elastic, abrasion resistant, diluted with isoparaffin.
Application	Initial treatment: Apply the oil sparingly to the dry surface with a spray bottle (max. 5–6 g/m ²). Then buff the surface with a single-brush floor care machine and a beige superpad. Work in sections (open time approx. 1 hour, replace pads as necessary). Intensive care: If the floor shows traces of use over time, you can carry out intensive care with naturaLin Oil. Thoroughly clean the floor with clean & green active (please follow the instructions given on the label) and then apply the fresh coat of oil as was done during the initial treatment. naturaLin Soap or clean & green natural is recommended for regular cleaning and care of the floor. Please wait two weeks after initial treatment or intensive treatment before applying the product.
Drying time	Can be walked on after about 24 h / 20°C Capable of taking foot traffic and completely dry after seven days / 20 °C Application temperature at least 18°C - max. 40°C
Coverage	1,000 ml for approx. 150 m ²
Durability	Shelf life of 24 months if stored in a cool, dry and frost-free location and kept in
Warning	Oxygen-drying oils can cause spontaneous combustion in combination with wood dust, cloths, pads and other absorbent work materials. These work materials must therefore be soaked with water and disposed of in an airtight container. Comply with local disposal regulations. Seal opened containers tightly and use quickly. No liability is assumed in case of improper or incorrect use and resulting damage.

Giscode:

KH 1



This technical data is provided for your information and guidance and is based on the current state of our knowledge. It does not represent any assurance of the described product's properties in terms of statutory warranty regulations.

Hamberger Flooring GmbH & Co. KG

Postfach 10 03 53

83003 Rosenheim

www.haro.com

Phone +49 8031 700-0

Fax +49 8031 700-199

e-mail: mail@hamberger.de